



## Outdoor IP55 Rated AP AP One Flex




### MIMO Directional Antenna

Forget about outboard antennas. The Flex has MIMO directional antennas built right in.



### Waterproof Enclosure

Provide 11ac Wi-Fi in more places with Flex. The tough IP55 rated enclosure is perfect for outdoor environments as well as other dusty and moist locations.



### 3-Port Switch

Connect to all of your devices, wired and wireless. Hooking up cameras, video surveillance, and even another AP One Flex is a breeze thanks to a built-in GE port and a PoE input.



**16  
SSID**

### User Access Control

Control network access with separate logins for each user group. AP One access points support up to 16 SSIDs, each with independent bandwidth limits and web blocking.



### InControl<sup>2</sup>

Setup. Manage. Report.  
Centrally manage multiple AP One units using InControl 2.



### AP Controller



Monitor and control the AP One with Balance's on-board AP controller.



### Centralised Management

Configure AP One access points onsite or from the cloud. Our AP Controller lets you locally manage access points from your Balance router, while InControl 2 offers a complete cloud-based solution accessible from any web-browser.




## Complete Network Solution

Enjoy better network integration and performance. AP One access points are a perfect complement to Balance routers, together providing blazing speed and superior reliability across your entire network.

## Social Wi-Fi Hotspot

Guests can now access your Wi-Fi hotspot with their Facebook login. In exchange, you can learn more about your customer base with insightful reports.

[Learn more about Social Wi-Fi Hotspot >](#)



## FEATURES

### Network

- Bridge Mode
- Router (NAT) Mode
- Wireless Distribution System (WDS)
- Support for PPPoE, Static IP, DHCP
- Management VLAN
- Spanning Tree Protocol

### Radio

- Multiple SSID
- Auto Channel Selection
- Transmit Power Adjustment
- Neighbour AP Detection

### Client Management

- Per SSID
  - VLAN with QoS (802.1p/802.1Q)

- Bandwidth Control
- MAC Address Filtering
- Layer 2 Client Isolation
- Limit on Max. Number of Client Per Client
  - VLAN with RADIUS
  - VLAN with VLAN Pool
  - Bandwidth Control
- Multicast Filter
- IGMP Snooping/Multicast Enhancement

### AP Security

- Open, WEP
- 802.1X with Dynamic WEP
- WPA2-Personal
- WPA2-Enterprise
- WPA/WPA2-Personal
- WPA/WPA2-Enterprise

### Complete VPN Solution

- PepVPN
  - Site-to-Site VPN
  - 256-bit AES Encryption
  - Pre-shared Key Authentication

### Captive Portal

- By InControl
- By Peplink AP Controller

### Device Management

- Web Administrative Interface
- InControl Cloud Management
- Peplink AP Controller
- SNMP v1, v2c and v3

### Certification



- FCC, CE, RoHS




## SPECIFICATIONS

- **Product Code:** APO-FLX
- **Ethernet Port:** 3x GE
- **Wi-Fi Standard:** Simultaneous 802.11ac wave 2/ac/a/n and 802.11b/g/n
- **Data Rates:** 2x2 MU-MIMO, 2.4 GHz: 300Mbps, 5 GHz: 866Mbps
- **Recommended Concurrent Users Per Radio:** 60
- **SSID Per Radio:** 16
- **Transmit Power:** 2412 - 2472 MHz: 20dBm, 5180 - 5825 MHz: 21dBm
- **Included Antenna:** Built-In MIMO Directional Antenna  
Antenna gain: 9dBi for 2.4GHz, 10dBi for 5GHz
- **Antenna Connector:** 2x RP-SMA Connectors (5GHz)
- **Enclosure:** Waterproof IP55 Outdoor
- **Dimensions:** 300 x 124 x 44.5 mm
- **Weight:** 520 grams
- **Power Input:** 802.3at PoE+ (56V Pepwave Passive PoE Input is Needed for full 1x 802.3at PoE+ LAN Output#)
- **Power Consumption:** 22W (max.)
- **Operating Temperature:** -40 - 55°C
- **Humidity:** 15% - 95% (non-condensing)
- **Certifications:** FCC, CE, RoHS
- **Warranty:** 1-Year Limited Warranty
- **Package Content:** AP One Flex

# 802.3at output requires the PoE injector (ACW-109), available separately.



Accessory – Wall/Pole Mount with Ball Joint for IP55 Outdoor Products<sup>^</sup>



<sup>^</sup> Available separately.



## ORDERING INFORMATION

Product Code	Product Name	Description
APO-FLX	AP One Flex	802.11 ac wave 2/ac/a/n 866Mbps and 802.11b/g/n 300Mbps. MIMO directional antennas: 2.4GHz, 8dBi (65° Horizontal x 60° Vertical); 5GHz, 10dBi (70° Horizontal x 30° Vertical). 3x 10/100/1000M Ethernet Ports with 1x 802.3at PoE Output option.

## FEATURE ADD-ON

Product Code	Feature Pack	Description
ACW-510	Ball Joint Mount for IP55 Outdoor Products	Wall/pole mount with flexible ball-joint for high-precision installation.

## PoE INJECTOR

Product Code	Description
ACW-107	802.3af/at PoE Injector (to power up the AP One Flex)
ACW-109	PoE Kit for IP55 Outdoor Products (to enable 802.3at PoE Output on the second port of AP One Flex)
ACW-622	Includes 1x 56V Power Supply Enables 802.3at/af PoE Output Ports (PoE License automatically applied after kit purchase)
SIM-BK8-4E-56V	SIM Injector, 8x SIM cards capacity, 4x 10/100/1000 LAN ports, 56V DC (compatible with HW revision 4 or above)

### Why Rising Connection is using equipment designed and built by Peplink?

- Industry leader in both ISP & Data Bonding across multiple technology platforms
- Reliable hardware from entry level professional equipment through to advanced Enterprises solutions
- Worldwide supported and local support here in Australia by fully trained technicians
- Reliable and secure redundancy paths for mission critical sites
- Designed for maximum possible business uptime

This demonstrates to Rising Connection that you will have the Quality, Reliability and Product Support.