




### Power up the B One 5G and get connected Instantly.









# Easy Integration 5G with Starlink and OneWeb

- Bond multiple LEO Satellite Services connections together
- Load Balance your LEO Satellite Services with other internet services (5G/LTE, Cable, Fiber, FWA)
- Optimise your network with additional features requested specifically by LEO Satellite Services

# Made for Fixed Wireless Access (FWA) with 5G

- Designed for use with MSP 5G/LTE Gateway devices
  - Bond various FWA together Australia: Telstra / Optus / TPG (Vodafone) New Zealand: Spark / OneNZ (Vodafone) / 2Degrees
  - Load Balance different internet sources (Cable, Fiber, 5G/LTE)
- Tether your phone with Wi-Fi WAN or USB





## Long Term Support

- Firmware is constantly updated to patch vulnerabilities and improve performance
- Futureproof your network as Peplink never ends support for older devices





## A Game Changer with SpeedFusion Connect

- With a valid PrimeCare subscription, take advantage of all of SpeedFusion features without the need for an advanced network setup
- Easy to set up and use with our Companion App



### **Key B One Benefits**




connected even when one of your Internet lines goes down technology seamlessly bonds multiple Internet connections into one more reliable Internet feed cellular modem backs up your primary wired connection or serves as your primary highspeed fixed-wireless connection

# Use Cases













# **Specifications**

- WAN Interface: 2 x 10/100/1000M Ethernet. 1 x Embedded Cellular Modem with a Redundant SIM Slot, 1 x USB-C Interface
- LAN Interface: 4x 10/100/1000M Ethernet
- Wi-Fi Interface: Simultaneous Dual-Band (2.4GHz / 5GHz), Wi-Fi 6, 2X2 MIMO, Wi-Fi WAN and/or AP
- SpeedFusion Features: Hot Failover<sup>1</sup>, WAN Smoothing<sup>1</sup>, Bandwidth Bonding<sup>1</sup>
- Number of SpeedFusion VPN Peers: 2 / 5<sup>1</sup>
- Router Throughput: 1 Gbps
- SpeedFusion VPN Throughput: No Encryption: 400 Mbps, 256-bit AES: 200 Mbps
- Recommended Users: 1 150
- AP Controller: Standard
- Maximum Number of AP Supported: 30 / 50 <sup>2</sup>
- Cellular Data Rate (Downlink /Uplink)<sup>3</sup>: 5G: 3.4 Gbps / 900 Mbps, CAT-20: 1.6 Gbps/ 200 Mbps
- Requires a PrimeCare subscription, complimentary for the first year. Available with licence add-on (AP-LC-50) 1.
- 2
- 3. Theoretical maximum data rates.

- Antenna Connectors: 4x SMA Cellular Connectors. 2x RP-SMA Wi-Fi Antenna Connectors
- Power Input: Power Port: 10V 30V DC AC Adapter: AC Input 100V-240V / DC Output 12V
- Power Consumption: 29W (max.)
- Dimensions: 262 x 161 x 33.5mm
- Weight: 756 grams
- Operating Temperature: -40° 45° C
- Humidity: 10% to 90% (non-condensing)
- Certifications: FCC, CE, RoHS
- SIM Options: Nano-SIM (4FF), Peplink eSIM, BYO eSIM (2 profiles)
- Warranty: 1-Year Limited Warranty
- Package Content: 1x B One 5G, 4x LTE/5G Antennas (ACW-235), 2x Dual Band Wi-Fi Antennas, 1x 12V 3A 4 Pin Power Supply



# Ordering Information

Product Code	Embedded Modems	Regions	5G Bands	LTE Bands
B-ONE-5GN-T-PRM	1x 5G	Global	5G (SA & NSA) Sub 6Ghz: n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n26, n28, n29, n30, n38, n40, n41, n48, n66, n70, n71, n75, n76, n77, n78, n79	B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B34, B38, B39, B40, B41, B42, B43, B46, B48, B66, B71

## Feature Add-on

Product Code	Description
PRM-B-1Y / PCP-B-1Y	PrimeCare B / PrimeCare+ B (1-Year)
PRM-B-2Y / PCP-B-2Y	PrimeCare B / PrimeCare+ B (2-Year)
PRM-B-4Y / PCP-B-4Y	PrimeCare B / PrimeCare+ B (4·Year)
ACW-634	10ft DC Power Cable
ANT-SLM-40G-S-B-6	Slim 40G - 4x4 MIMO 5G Ready Cellular Antenna System with GPS (Black)
ANT-MB-42G-S-W-6	Mobility 42G - 4x4 MIMO 5G Ready Cellular Antenna System with Wi-Fi and GPS (White)
ANT-MB-42G-S-B-6	Mobility 42G - 4x4 MIMO 5G Ready Cellular Antenna System with Wi-Fi and GPS (Black)



## **Deep Dive**

#### Software

Pepwave MAX Firmware

#### WAN

Support for PPPoE, Static IP, DHCP WAN Link Health Check Bandwidth Allowance Monitor Support for Dynamic DNS services

#### LAN

DHCP Server for LAN Clients Extended DHCP Option DHCP Reservation DNS Proxy for LAN Clients VLAN on LAN Support

#### Security

Stateful Firewall DoS Prevention Web Blocking

#### **Complete VPN Solution**

SpeedFusion VPN/SpeedFusion

- Hot Failover
- Site-to-Site VPN
- 256-bit AES Encryption
- Pre-shared Key Authentication
- Dynamic Routing

X.509 Certificate Support IPsec VPN (Network-to-Network)

#### **Advanced QoS**

Individual Bandwidth Limit Application Prioritisation

- SIP, HTTPS, VPN QoS
- Custom Application QoS

#### Networking

NAT and IP Forwarding Static Routes Port Forwarding Many to One, One to One NAT NAT Pool SIP ALG, H.323 ALG UPnP, NAT-PMP

#### **AP Controller**

Support for Pepwave AP Series Auto AP Discovery Auto AP Firmware Management AP Profile Configuration Wi-Fi Usage Statistics

#### **Captive Portal Support**

Support for Wired and Wireless LAN clients Support RADIUS Authentication Time and Usage Quotas on Open Access Mode Built-in Customisable Splash Page

#### **Device Management**

Web Administrative Interface Command Line Interface InControl Cloud Management Email Notification Active Client & Session Lists Bandwidth Usage Statistics Syslog Service SNMP v1, v2c and v3

Trademarks and registered trademarks are the property of Rising Connection Pty Ltd, Peplink or their respective owners. Specifications are subject to change without notice. Images shown may vary slightly from the actual product.

Rising.AU